

60300F

Fingerprint Video Intercom Access

- > Waterproof, conforms to IP65
- > Metal housing, anti-vandal
- > Card type: EM Card
- > iOS and Android available
- > Add / Delete users by APP
- > Can set Time Restriction for users
- > Support checking Opening Record
- > Remotely Access (Support 3G/4G/5G)
- > Support video calling and surveillance
- > Full duplex voice intercom

User Capacity Common User Visitor User	Hardware User: 1000 APP User: 500 990 (100 Fingerprint Users + 890 Card Users) 10
Operating Voltage Idle Current Active Current	12~18V DC ≤ 60mA ≤ 150mA
Proximity Card Reader Radio Technology Read Range	EM 125KHz 2~6cm
Wiring Connections	Relay output, exit button, Wiegand input/output
Relay Adjustable Relay Output Time Lock Output Load	One (NO, NC, Common) 0~99 Seconds (5 seconds default) 2 Amp Maximum
Wiegand Interface	Wiegand 26~44 bits input & output (Factory default: Wiegand 26bits)

Environment Operating Temperature Operating Humidity	Meets IP65 -30°C ~ 60°C (-22°F ~ 140°F) 0%RH ~ 92%RH
Physical Color Dimensions Unit Weight Shipping Weight	Zinc-Alloy Sliver & Black L142 x W48 x H22 (mm) 315g 410g

60300KPC

- Keypad Video Intercom Access
- > Waterproof, conforms to IP65
 - > Metal housing, anti-vandal
 - > Card type: EM Card
 - > iOS and Android available
 - > Add / Delete users by APP
 - > Can set Time Restriction for users
 - > Support checking Opening Record
 - > Remotely Access (Support 3G/4G/5G)
 - > Support video calling and surveillance
 - > Full duplex voice intercom

User Capacity Common User Visitor User	Hardware User: 1000 990 (PIN/Card Users) 10	APP User: 500
PIN Length	4~6 digits	
Operating Voltage Idle Current Active Current	12~18V DC ≤ 60mA ≤ 150mA	
Proximity Card Reader Radio Technology Read Range	EM 125KHz 2~6cm	
Wiring Connections	Relay output, exit button, Wiegand input/output	

Relay Adjustable Relay Output Time Lock Output Load	One (NO, NC, Common) 0~99 Seconds (5 seconds default) 2 Amp Maximum
Wiegand Interface PIN Output	Wiegand 26~44 bits input & output (Factory default: Wiegand 26bits) 4 bits,8bits (ASCII),10 digits Virtual Number(Factory default:4bits)
Environment Operating Temperature Operating Humidity	Meets IP65 -40°C ~ 60°C (-40°F ~ 140°F) 0%RH ~ 92%RH
Physical Color Dimensions Unit Weight Shipping Weight	Zinc-Alloy Sliver & Black L142 x W48 x H22 (mm) 315g 410g

60300C

RFID Video Intercom Access

- > Waterproof, conforms to IP65
- > Metal housing, anti-vandal
- > Card type: EM Card
- > iOS and Android available
- > Add / Delete users by APP
- > Can set Time Restriction for users
- > Support checking Opening Record
- > Remotely Access (Support 3G/4G/5G)
- > Support video calling and surveillance
- > Full duplex voice intercom

User Capacity Common User Visitor User	Hardware User: 1000 990 10	APP User: 500
Operating Voltage Idle Current Active Current	12~18V DC ≤ 60mA ≤ 150mA	

Proximity Card Reader Radio Technology Read Range	EM 125KHz 2~6cm
Wiring Connections	Relay output, exit button, Wiegand input/output
Relay Adjustable Relay Output Time Lock Output Load	One (NO, NC, Common) 0~99 Seconds (5 seconds default) 2 Amp Maximum
Wiegand Interface	Wiegand 26~44 bits input & output (Factory default: Wiegand 26bits)
Environment Operating Temperature Operating Humidity	Meets IP65 -40°C ~ 60°C (-40°F ~ 140°F) 0%RH ~ 92%RH
Physical Color Dimensions Unit Weight Shipping Weight	Zinc-Alloy Sliver & Black L142 x W48 x H22 (mm) 315g 410g